

# Performance-PRO™ XT

manual ambulance cot

stryker®



## Standard Features

- Color-coded controls
- High visibility powder-coated frame
- Lightest-in-class, all-aluminum X-frame
- Scientifically optimized lift bar and control design
- Lower lifting bar
- Lift-capable safety bar
- Integrated bumper system
- Perforated litter surface
- One-hand release, retractable head section
- One-hand release, fold-down side rails
- One-hand release, infinite positioning, pneumatically assisted backrest
- Oversized wheels with sealed caster and wheel bearings
- Sealed bolster mattress
- Shock or flat leg positioning
- Two lap belts and one four-point shoulder restraint
- Single wheel lock
- Side release handle
- Built-in pull handle
- X-frame guards
- Power washable
- Load height adjustment

## Optional Features

- Heavy duty two- or three-stage IV poles (patient right or left)
- Permanent or removable O<sub>2</sub> bottle holders (head end, foot end or fowler)
- Defibrillator platform
- Dual wheel locks
- Pedi-Mate® restraint package
- Equipment hook
- Backrest storage pouch
- Head-end storage flat
- Base storage net
- Knee gatch
- Head extension
- Pillow
- Restraint extender
- Power-LOAD™ compatibility

## Specifications

<b>Model Number</b>	<b>6086</b>
<b>Height<sup>1</sup></b>	
Position 1	13.8 in (35 cm)
Position 2	22 in (56 cm)
Position 3	25.8 in (66 cm)
Position 4	28.1 in (71 cm)
Position 5	31.9 in (81 cm)
Position 6	34.6 in (88 cm)
Position 7	37.3 in (95 cm)
Position 8	40 in (102 cm)
Position 9	42.2 in (107 cm)
<b>Load Height Adjustment</b>	
High	Deck heights 32 in (81 cm) and above
Mid	Deck heights between 30 – 32 in (76 – 81 cm)
Low	Deck heights below 30 in (76 cm)
<b>Length</b>	
Standard	80 in (203 cm)
Minimum	64 in (163 cm)
<b>Width</b>	23 in (58 cm)
<b>Weight<sup>2</sup></b>	89 lb (40 kg)
<b>Wheels</b>	
Diameter	6 in (15 cm)
Width	2 in (5 cm)
<b>Articulation</b>	
Backrest	0 – 73°
Shock Position	+15°
Optional Knee Gatch	30°
<b>Maximum Weight Capacity</b>	700 lb (318 kg)
<b>Minimum Operator Required</b>	
Occupied Cot	2
Unoccupied Cot	1
<b>Recommended Fastener System</b>	
Power-LOAD™	Model 6390
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371
<b>Recommended Loading Height<sup>3</sup></b>	Up to 34 in (86 cm)

## Warranty

- One-year parts, labor and travel or two-year parts only
- One-year soft goods
- Three-year X-frame components
- Lifetime on all welds\*

### Extended warranties available.

7-year service life.

<sup>1</sup>Height measured from bottom of mattress, at seat section, to ground level.

<sup>2</sup>Cot is weighed without mattress and restraints.

<sup>3</sup>Load height can be set between 27.25 in and 34 in.

Stryker reserves the right to change specifications without notice.

In-service video included with every order.

The Performance-PRO XT is designed to conform to the Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The Performance-PRO XT is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.

Patents pending.

Power-LOAD Compatibility option currently not available, specifications subject to change.

Pending 510(K) clearance, not available for sale.

## EMS Equipment

3800 E. Centre Ave.  
Portage, MI 49002 U.S.A.  
t: 269 389 2100 f: 269 329 2315  
toll free: 800 784 4336

www.ems.stryker.com

Planned Certification

