

Speed-Sheet™
patient transfer and barrier sheet

Reduce the risk of injuries
when transferring patients

EMS Equipment

3800 E. Centre Ave.
Portage, MI 49002 U.S.A.
t: 269 389 2100 f: 866 795 2233
toll free: 800 784 4336

www.ems.stryker.com



Standard Features

- GRIP to SLIP™ technology
- Disposable
- Fluid impermeable
- Full length
- Latex free
- Single sheet packaging

Speed-Sheet Single

Model Number 6010-001-012

Speed-Sheet Specifications

Length	72 in (183 cm)
Width	23.5 in (60 cm)
Activating Tabs	8
Use Cycle	Single use, once activated
Maximum Weight Capacity	700 lb (318 kg)

Single Sheet Packaging Specifications

Capacity	1 Speed-Sheet
Length	12.5 in (31.8 cm)
Width	9 in (22.9 cm)
Height	.5 in (1.3 cm)
Weight, including 1 Speed-Sheet	.4 lb (.18 kg)
Storage Temperature	-4° - 104°F (-20° - 40°C)
Storage Relative Humidity	0% - 100%

Stryker reserves the right to change specifications without notice.

The information presented in this brochure is intended to demonstrate a Stryker product. Always refer to the package insert, product label and/or user instructions before using any Stryker product. Products may not be available in all markets. Product availability is subject to the regulatory or medical practices that govern individual markets. Please contact your Stryker Account Manager if you have questions about the availability of Stryker products in your area.

Products referenced with ® designation are trademarks of Stryker.
Products referenced with ® designation are registered trademarks of Stryker.
The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.



Certification



Copyright © 2011 Stryker
DDM/RRP 1M 0610, 09-SEM-2981
Mkt Lit-414 20 APR 2010 Rev C