

## Reduce the risk of injuries when raising and lowering



### EMS Equipment

3800 E. Centre Ave.  
Portage, MI 49002 U.S.A.  
t: 269 389 2100 f: 269 329 2315  
toll free: 800 784 4336

www.ems.stryker.com

### Standard Features

- Manual back-up release handle
- Automatic high-speed retract
- Battery-powered hydraulic lift system
- Preventative maintenance hour meter
- Battery pack power level indicator
- Color-coded controls
- High visibility powder-coated frame
- Lightweight, rugged aluminum construction
- Lift-capable safety bar
- Scientifically optimized lift bar and control design
- Integrated bumper system
- Retractable head section
- Oversized wheels with sealed caster and wheel bearings
- Built-in pull handle
- X-frame guards
- Power washable
- Tie down brackets
- Compatible with airsled or equivalent configurations
- SMRT power system (12V DC, 120V AC and 240V AC options available)

### Optional Features

- Rigid push bars
- Dual wheel locks
- Litter extension
- Head end storage flat
- Base storage net
- SMRT charger mounting bracket
- Power-LOAD™ compatibility

### Compatibility

- Airborne Stackable
- Airborne Side-by-Side
- Dräger Stackable
- Dräger Extended
- No adapter option

### Specifications

<b>Model Number</b>	<b>6516</b>
<b>Height<sup>1</sup></b> (infinite height positioning between lowest and highest position)	
Highest Position	41.5 in (105 cm)
Lowest Position	14 in (36 cm)
<b>Length</b>	
Standard	63 in (160 cm)
Maximum	81 in (206 cm)
<b>Width</b>	23 in (58 cm)
<b>Weight<sup>2</sup></b>	134 lb (61 kg)
<b>Wheels</b>	
Diameter	6 in (15 cm)
Width	2 in (5 cm)
<b>Maximum Weight Capacity</b>	700 lb (318 kg)
<b>Minimum Operators Required</b>	
Occupied Cot	2
Unoccupied Cot	1
<b>Recommended Fastener System</b>	
Power-LOAD™	Model 6390
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371
<b>Recommended Loading Height<sup>3</sup></b>	Up to 36 in (91 cm)

### Warranty

- Two-year parts, labor and travel
- One-year soft goods
- Three-year X-frame components
- Three-year limited powertrain
- Lifetime on all welds\*

Extended warranties available.

\*7-year service life.

<sup>1</sup> Height measured from the top of cot, at the center point, to ground level.

<sup>2</sup> Cot is weighed with one battery pack, without incubator.

<sup>3</sup> Can accommodate load decks up to 36 in. Load height can be set between 26 in and 36 in.

Stryker reserves the right to change specifications without notice.

In-service video included with each order.

The Power-PRO IT is recognized by Underwriters Laboratory to IEC-60601-1.

The Power-PRO IT is designed to conform to Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The Power-PRO IT is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.

Patents pending.

Power-LOAD Compatibility option currently not available, specifications subject to change. Pending 510(K) clearance, not available for sale.

The device has not been authorized as required by the rules of the Federal Communications Commission. The device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

### Planned Certifications

CE cRUus IPX6 IEC-60601-1



Copyright © 2011 Stryker  
DDM/PDF 0411, 10-SEM-3284  
Mkt Lit-147-27 Jun 2006 Rev D