



stryker®

EMS Equipment



Power-PRO™ TL
powered
ambulance cot

Power-PRO TL

powered
ambulance cot

Shown with optional accessories.

Reduce the risk of injuries when raising and lowering

Power-PRO TL reduces risk of cumulative trauma injuries, and lost or modified workdays.

Caregivers experience frequent spinal loading due to repetitive lifting and lowering, bending, and carrying. The Power-PRO TL reduces spinal loading that can result in injury from these repetitive actions. Reduce the risk of lost and modified workdays. Because the Power-PRO TL can increase length of careers while improving retention and recruitment, it is now the industry standard of care.

- **Innovative battery-powered hydraulic system raises and lowers the patient with the touch of a button**
- **Easy manual back-up for all powered functions**
- **Retractable head section reduces footprint in tight spaces for easy maneuverability**
- **Reduces risk of injuries and lost or modified workdays**

318kg/700lb
capacity

Certifications



IPX6 IEC-60601-1
BS EN-1789



Rigid Push Bars (optional)

A Stryker exclusive. Unprecedented maneuverability in any situation.



Pneumatically Assisted Backrest

A Stryker innovation. Significantly reduces operator effort and increases patient comfort.



Fold-Down Side Rails

A Stryker innovation. Side rails are designed to provide patients with a greater sense of security.



Hydraulic Lift System

Battery-powered hydraulic lift system with manual back-up for operator confidence.



Steer-Lock System

Wheel can swivel or lock into straight-line position, maximizing maneuverability.





Retractable Head and Foot Sections

A Stryker exclusive. Maximizes maneuverability in tight spaces.



Shock, Flat Leg, or Optional Knee Gatch Positioning

Knee gatch provides patient comfort and greater lift clearance.

Bolster Mattress

The Stryker-preferred sealed bolster mattress provides patients a greater sense of security during transport.



Battery Pack Release Control

Accessible and easily changed in any situation.

Patented X-frame

Proven reliability. Will **NOT** "hot drop."

Warranty

- One-year parts, labor, and travel or two-year parts only
- Lifetime on all welds*

* 7-year service life

Oversized Wheels

Requires less force to roll, improving maneuverability over rough terrain.



Cot Fastener System

Welded stainless steel construction for unprecedented durability. Available in floor-plate and floor-track mounting configurations.

Select Features



Power Controls

Contoured control buttons for instant touch recognition and ease of operation.

Manual Back-up Release Handle

Allows nonpowered operation of all powered cot functions.



SMRT™ Power System

Automatic power management, zero memory, and in-vehicle charging.



Marine-grade Hydraulic System

Provides reliable operation in harsh conditions.



Power-PRO TL Specifications

Model Number	6550
Height¹ (infinite height positioning between lowest and highest position)	
Highest Position	41.5 in (105 cm)
Lowest Position	14 in (36 cm)
Overall Length	81 in (206 cm)
Length	
Standard	76.5 in (194.3 cm)
Minimum	55 in (139.7 cm)
Width	145 in (58 cm)
Weight²	145 lb (66 kg)
Wheels	
Diameter	6 in (15 cm)
Width	2 in (5 cm)
Articulation	
Backrest	0–75°
Shock Position	+15°
Optional Knee Gatch	30°
Maximum Weight Capacity	700 lb (318 kg)
Minimum Operator Required	
Occupied Cot	2
Unoccupied Cot	1
Recommended Cot Fastener System	
Floor Mount ³	Model 6385, 6386, 6387

¹ Height measured from bottom of mattress, at seat section, to ground level.

² Cot is weighed with one battery pack, without mattress and restraints.

³ Designed to be compatible with competitive ambulance cots. Floor plate and floor track mounting configurations available.

The Power-PRO TL is designed to be compatible with competitive cot fastener systems.

Stryker reserves the right to change specifications without notice.

In-service video included with each order.

International patents pending.

Optional Features

- Heavy duty two- and three-stage IV poles (patient right or left)
- Restraint extender (91.4 cm/36 in)
- Rigid push bars (removable)
- Removable O₂ bottle holder
- Base storage net
- Pocketed backrest storage pouch
- Equipment hook
- Four corner wheel locks
- SMRT Charger mounting bracket
- Knee gatch
- Defibrillator platform
- Transfer Flat
- Pedi-Mate™ restraint package

The information presented in this brochure is intended to demonstrate a Stryker product. Always refer to the package insert, product label and/or user instructions before using any Stryker product. Products may not be available in all markets. Product availability is subject to the regulatory or medical practices that govern individual markets. Please contact your Stryker Account Manager if you have questions about the availability of Stryker products in your area.

Products referenced with ™ designation are trademarks of Stryker.

Products referenced with * designation are registered trademarks of Stryker.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.

Mkt Lit-145 01 Rev E
DDM/RRP 0811
Copyright © 2011 Stryker
Printed in U.S.A.

stryker[®]

Joint Replacements

Trauma, Extremities & Deformities

Craniomaxillofacial

Spine

Biologics

Surgical Products

Neuro & ENT

Interventional Spine

Navigation

Endoscopy

Communications

Imaging

Patient Care & Handling Equipment

EMS Equipment

Stryker UK Limited
Stryker House
Hambridge Road
Newbury, Berkshire
RG14 5EG, UK

t: +44 (0) 1635 262444
f: +44 (0) 1635 36400
PHE@stryker.com

www.ems.stryker.com
www.stryker.co.uk