



EMS Equipment

3800 E. Centre Ave.
Portage, MI 49002 U.S.A.
t: 269 329 2100 f: 269 329 2315
toll free: 800 784 4336

www.ems.stryker.com

Standard Features

- Transport at load height capability
- Positive action height adjustment
- Easy-to-use release handle design
- Color-coded controls
- Dampened action during hot drops
- Lap belt extensions
- High visibility powder-coated frame
- Lightweight, rugged aluminum construction
- Scientifically optimized lift bar design
- Lower lifting bar
- Seven height positions
- Integrated bumper system
- Lift-capable safety bar
- Perforated litter surface
- One-hand release breakaway head section with safety bar
- Floor-mounted safety hook
- One-hand release, fold-down side rails
- One-hand release, infinite positioning, pneumatically assisted backrest
- Oversized wheels with sealed caster and wheel bearings
- Reflective labeling
- Sealed flat mattress
- Shock positioning
- Two lap belts and one four-point shoulder restraint

Optional Features

- Heavy duty two or three-stage IV poles (patient right or left)
- Base storage tray
- Nonpocketed head end storage
- Height limit kit*
- Permanent or removable oxygen bottle holders (foot end)
- Rigid head and foot end push/pull handles
- Single or dual wheel lock
- X-frame guards
- Patient security straps
- Side lift handles
- Tow package
- Transfer Flat (9 ft. x 5 ft., 1,600 lb. capacity)

Specifications

Model Number	6083
Height¹	
Position 1	13.5 in. (34 cm)
Position 2	24.5 in. (62 cm)
Position 3	27.5 in. (70 cm)
Position 4	30 in. (76 cm)
Position 5	32.5 in. (83 cm)
Position 6	34.5 in. (88 cm)
Position 7	37 in. (94 cm)
Length	
Standard	80 in. (203 cm)
Minimum	62 in. (157 cm)
Width	29 in. (74 cm)
Weight²	111 lb. (50 kg)
Wheels	
Diameter	6 in. (15 cm)
Width	2 in. (5 cm)
Articulation	
Backrest	0 – 73°
Shock Position	+14°
Maximum Weight Capacity³	1600/850 lb. (725/385 kg)
Minimum Operator Required	
Occupied Cot	2
Unoccupied Cot	1
Recommended Fastener System	
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371
Recommended Loading Height⁴	Up to 33 in. (84 cm)

Warranty

- One year parts, labor and travel or two years parts
- Lifetime on all welds*

Extended warranties available.

*5-year service life.

¹Height limit kit recommended for load heights less than 28 inches (71 cm). High height kit recommended for load heights more than 32 inches (81 cm).

¹Height measured from bottom of mattress at seat section to ground level.

²Cot is weighed without mattress and restraints.

Stryker reserves the right to change specifications without notice.

In-service video included with every order.

The MX-PRO Bariatric Transport is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.