

Reduce the risk of injuries when on the stairs



EMS Equipment

3800 E. Centre Ave.
Portage, MI 49002 U.S.A.
t: 269 329 2100 f: 269 329 2315
toll free: 800 784 4336

www.ems.stryker.com

Standard Features

- High visibility powder-coated frame
- Color-coded controls
- Extendable foot end lift handles
- Locking rear lift handles
- Molded hand grips
- Lightweight, rugged aluminum construction
- Oversized rear wheels with sealed bearings
- Dual wheel locks
- Compact storage size
- Positive action locking mechanism
- Power washable
- Grease-free maintenance

Model 6250 Standard Features

- Conforms to BS EN 1865

Model 6251 Standard Features

- 4-inch (10 cm) front caster wheels

Model 6252 Standard Features

- Innovative Stair-TREAD™ system
- Extendable upper control handle
- 4-inch (10 cm) front caster wheels

Optional Features

- Two-piece molded ABS seat
- One-piece traditional vinyl seat
- Color-coded patient restraints⁴ (plastic buckles)
- Nonabsorbent patient restraints⁴ (metal buckles)
- Polyester patient restraints⁴ (metal buckles)
- Patient head support (model 6252 only)
- O₂ bottle holder
- Vinyl head support
- Polypropylene head support
- IV clip
- Foot support

Specifications¹

Models	6250	6251	6252
Height	36 in. (91 cm)	36 in. (91 cm)	37.5 in. (95 cm)
Width	20.5 in. (52 cm)	20.5 in. (52 cm)	20.5 in. (52 cm)
Depth ²	28 in. (71 cm)	28 in. (71 cm)	28 in. (71 cm)
Folded Depth	8 in. (20 cm)	8 in. (20 cm)	8 in. (20 cm)
Weight	20 lb. (9 kg)	23 lb. (10 kg)	31.5 lb. (14 kg)
Maximum Load ³	500 lb. (226 kg)	500 lb. (226 kg)	500 lb. (226 kg)

Warranty

- One year parts, labor and travel or two years parts
- Lifetime on all welds*

Extended warranties available.

*7-year service life.

¹Dimensions are measured from the outermost edges of the main frame. Specifications are rounded to the nearest whole number. Conversions are calculated before rounding.

²Depth dimensions are measured with extendable handles retracted.

³Maximum load capacity is total weight distributed in accordance to basic human anatomy. EMTs must consider the weight of the patient, equipment and accessories when determining the total weight on the product.

⁴Patient restraint set includes two cross-chest restraints and one ankle restraint. Cross-chest restraints can also be used in a chest and lap restraint configuration.

In-service video included with every order.

Stryker reserves the right to change specifications without notice.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.